

MANY APPLICATIONS ONE SOLUTION

LPT 810 CR X BS4



Beverages



Fish



FMCG



Fruits
& Vegetables



Milk &
Dairy



Cement



Industrial
Components









8.72 TONS
GVW

Description LPT 810 CR X

Engine	TATA 497 TCIC BSIV CR X
Power	93.2 kW (125 PS) @ 2400 r/min
Torque	400 Nm @ 1300-1600 r/min
Clutch	Single Plate Dry Friction Type (Booster-assisted) - 310 mm
Gearbox	TATA GBS 550 6F-1R
Front Axle	Heavy Duty Forged I Beam; Reverse Elliot Type
Rear Axle	Single Reduction Hypoid Gears, Fully Floating Axle
Tyre Size (Front/Rear)	7.50 x 16 - 16 PR Rib, Lug
Steering Type	Integral Hydraulic Power Steering
Front Suspension	Semi-elliptical Leaf Springs & Hydraulic Double Acting Telescopic Type Shock Absorber
Rear Suspension	Semi-elliptical Leaf Springs With Auxiliary Springs & Hydraulic Double Acting Telescopic Type Shock Absorber
Brakes	Dual Circuit, Full S cam Air Brakes
Parking Brake	Spring Actuated Parking Brake acting on Rear Wheels
Engine Brake	Coupled with Service Brake
Min. Ground clearance	205 mm
Gradeability	30%
Max. Speed	80 km/h
Battery	12 V, 100 Ah
Fuel Tank Capacity	160 l
GVW	8720 kg

Dimensions

						
	CLB	High Deck	CAB	CLB	High Deck	CAB
Wheelbase		3400 mm			3800 mm	
Deck Length		14 ft			17 ft	
Turning Circle Radius		6150 mm			6750 mm	
Length	4381 mm	4342 mm	NA	5050 mm	5062 mm	NA
Width	2042 mm	2014 mm	NA	2042 mm	2074 mm	NA
Height	603 mm	1773 mm	NA	603 mm	1713 mm	NA
Loading Area	9 sq. m.	9 sq. m.	NA	10.3 sq. m.	10.5 sq. m.	NA
Warranty	3 years or 3 lakh km, whichever is earlier*					

Advantages



LOW ON MAINTENANCE




INCREASED EARNINGS



AIR BRAKES



COMFORT ASSURED



HIGH HORSEPOWER AND TORQUE



HEAVY DUTY AGGREGATES



CR X Delighters:

Digital Clock, Portable & Clear Lens Lamp, Shirt Hook, Mobile Charger, Rear View Mirror, Utility Box, Reverse Beeper



CAUTION: Do not weld or drill on chassis frame. Accessories shown in the picture or elsewhere do not constitute standard fitments. The specifications are indicative. Due to continuous product improvements, these specifications are liable to change without notice.

For more information, please visit our website: www.tatamotors.com. You can also contact our Sales Office: You can also contact our Sales Office: Tata Motors Limited, 4th Floor, Ahura Centre, 82, Mahakali Caves Road, MIDC, Andheri (East), Mumbai 400093 or call toll-free no. 18002097979. *Terms & conditions apply

Dealer Stamp